

Product datasheet

Specifications

CLIPSAL



Timer Switch' 250V 15A, Standard Series, 24 Hour Timer

TC32V24-WE

⚠ To be discontinued

Main

Product brand	Clipsal
Assembly Type	Basic element with full cover plate

Complementary

[Ue] rated operational voltage	250 V AC
Rated current	15 A
Marking	ON-OFF

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.2 cm
Package 1 Width	7.8 cm
Package 1 Length	12.8 cm
Package 1 Weight	230 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	250 cm
Package 2 Width	214 cm
Package 2 Length	338 cm
Package 2 Weight	4.7 kg

Contractual warranty

Warranty (in months)	18
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0.9 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	146 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	13
Take-back	No